

ステンレス鋼管 (SUS304) 自立型・段継ポール

- カップリング、導線引出金物を取付済みです。
- 設置条件に応じ、計算してください。
計算方法は建築基準施行令第87条に規定する風圧に耐える強度を有すものとする。
- 一段目鋼管長さは、4mとなります。

標準寸法表

品番	旧品番	全長 L m	一段目 D1 (厚) × L1 mm m	二段目 D2 (厚) × L2 mm m	重量 kg
CCBBA010004	—	3.0	48.6(3) × 3.0		10.2
CCBBA010014	—	〃	60.5(3) × 3.0		12.9
CCBBA010024	—	〃	76.3(3) × 3.0		16.4
CCBBA010005	N4060	3.5	48.6(3) × 3.5		11.9
CCBBA010015	—	〃	60.5(3) × 3.5		15.0
CCBBA010025	—	〃	76.3(3) × 3.5		19.2
CCBBA010006	—	4.0	48.6(3) × 4.0		13.6
CCBBA010016	N4061	〃	60.5(3) × 4.0		17.2
CCBBA010026	—	〃	76.3(3) × 4.0		21.9
CCBBA020000	—	4.5	60.5(3) × 4.0	48.6(3) × 0.5	20.6
CCBBA020010	—	〃	76.3(3) × 4.0	48.6(3) × 0.5	25.3
CCBBA020020	—	〃	76.3(4) × 4.0	48.6(3) × 0.5	32.2
CCBBA020030	—	〃	76.3(3) × 4.0	60.5(3) × 0.5	26.2
CCBBA020040	—	〃	89.1(3) × 4.0	60.5(3) × 0.5	30.0
CCBBA020050	—	〃	89.1(4) × 4.0	60.5(3) × 0.5	38.2
CCBBA020060	—	〃	89.1(3) × 4.0	48.6(3) × 0.5	29.1
CCBBA020070	—	〃	101.6(4) × 4.0	60.5(3) × 0.5	43.2
CCBBA020001	—	5.0	60.5(3) × 4.0	48.6(3) × 1.0	22.3
CCBBA020011	—	〃	76.3(3) × 4.0	48.6(3) × 1.0	27.0
CCBBA020021	—	〃	76.3(4) × 4.0	48.6(3) × 1.0	33.9
CCBBA020031	—	〃	76.3(3) × 4.0	60.5(3) × 1.0	28.4
CCBBA020041	—	〃	89.1(3) × 4.0	60.5(3) × 1.0	32.2
CCBBA020051	—	〃	89.1(4) × 4.0	60.5(3) × 1.0	40.4
CCBBA020061	—	〃	89.1(3) × 4.0	48.6(3) × 1.0	30.8
CCBBA020071	—	〃	101.6(4) × 4.0	60.5(3) × 1.0	45.3
CCBBA020002	—	5.5	60.5(3) × 4.0	48.6(3) × 1.5	24.0
CCBBA020012	N4072	〃	76.3(3) × 4.0	48.6(3) × 1.5	28.7
CCBBA020022	—	〃	76.3(4) × 4.0	48.6(3) × 1.5	35.6
CCBBA020032	—	〃	76.3(3) × 4.0	60.5(3) × 1.5	30.5
CCBBA020042	—	〃	89.1(3) × 4.0	60.5(3) × 1.5	34.3
CCBBA020052	—	〃	89.1(4) × 4.0	60.5(3) × 1.5	42.5
CCBBA020062	—	〃	89.1(3) × 4.0	48.6(3) × 1.5	32.6
CCBBA020072	—	〃	101.6(4) × 4.0	60.5(3) × 1.5	47.5
CCBBA020003	—	6.0	60.5(3) × 4.0	48.6(3) × 2.0	25.7
CCBBA020013	—	〃	76.3(3) × 4.0	48.6(3) × 2.0	30.4
CCBBA020023	—	〃	76.3(4) × 4.0	48.6(3) × 2.0	37.3
CCBBA020033	—	〃	76.3(3) × 4.0	60.5(3) × 2.0	32.7
CCBBA020043	—	〃	89.1(3) × 4.0	60.5(3) × 2.0	36.5
CCBBA020053	—	〃	89.1(4) × 4.0	60.5(3) × 2.0	44.7
CCBBA020063	—	〃	89.1(3) × 4.0	48.6(3) × 2.0	34.3
CCBBA020073	—	〃	101.6(4) × 4.0	60.5(3) × 2.0	49.6
CCBBA020004	—	6.5	60.5(3) × 4.0	48.6(3) × 2.5	27.4
CCBBA020014	—	〃	76.3(3) × 4.0	48.6(3) × 2.5	32.1
CCBBA020024	—	〃	76.3(4) × 4.0	48.6(3) × 2.5	39.0
CCBBA020034	—	〃	76.3(3) × 4.0	60.5(3) × 2.5	34.8
CCBBA020044	—	〃	89.1(3) × 4.0	60.5(3) × 2.5	38.6
CCBBA020054	N4073	〃	89.1(4) × 4.0	60.5(3) × 2.5	46.8
CCBBA020064	—	〃	89.1(3) × 4.0	48.6(3) × 2.5	36.0
CCBBA020074	—	〃	101.6(4) × 4.0	60.5(3) × 2.5	51.8
CCBBA020005	—	7.0	60.5(3) × 4.0	48.6(3) × 3.0	29.1
CCBBA020015	—	〃	76.3(3) × 4.0	48.6(3) × 3.0	33.8
CCBBA020025	—	〃	76.3(4) × 4.0	48.6(3) × 3.0	40.7
CCBBA020035	—	〃	76.3(3) × 4.0	60.5(3) × 3.0	36.9
CCBBA020045	—	〃	89.1(3) × 4.0	60.5(3) × 3.0	40.8
CCBBA020055	N4063	〃	89.1(4) × 4.0	60.5(3) × 3.0	49.0
CCBBA020065	—	〃	89.1(3) × 4.0	48.6(3) × 3.0	37.7
CCBBA020075	—	〃	101.6(4) × 4.0	60.5(3) × 3.0	53.9
CCBBA020006	—	7.5	60.5(3) × 4.0	48.6(3) × 3.5	30.8
CCBBA020016	—	〃	76.3(3) × 4.0	48.6(3) × 3.5	35.5
CCBBA020026	—	〃	76.3(4) × 4.0	48.6(3) × 3.5	42.4
CCBBA020036	—	〃	76.3(3) × 4.0	60.5(3) × 3.5	39.1
CCBBA020046	—	〃	89.1(3) × 4.0	60.5(3) × 3.5	42.9
CCBBA020056	—	〃	89.1(4) × 4.0	60.5(3) × 3.5	51.1
CCBBA020066	—	〃	89.1(3) × 4.0	48.6(3) × 3.5	39.4
CCBBA020076	N4074	〃	101.6(4) × 4.0	60.5(3) × 3.5	56.1

